



US005898801A

United States Patent [19]**Braun et al.**[11] **Patent Number:** **5,898,801**[45] **Date of Patent:** **Apr. 27, 1999**[54] **OPTICAL TRANSPORT SYSTEM**

[75] Inventors: **Steve W. Braun**, Leucadia; **Henri Hodara**, Dana Point, both of Calif.; **John J. Soderberg**, Acworth; **G. Allan Whittaker**, Alpharetta, both of Ga.

[73] Assignee: **Lockheed Martin Corporation**, Bethesda, Md.

[21] Appl. No.: **09/014,079**

[22] Filed: **Jan. 29, 1998**

[51] Int. Cl.⁶ **G02B 6/28; H04B 10/20**

[52] U.S. Cl. **385/24; 359/119; 359/127; 359/134**

[58] Field of Search **385/24, 27, 31, 385/45, 47, 37, 17; 372/6; 359/115, 119, 127, 134, 143, 125, 137**

[56] **References Cited****U.S. PATENT DOCUMENTS**

5,572,612	11/1996	Delavaux et al.	385/24
5,712,932	1/1998	Alexander et al.	385/24
5,764,821	6/1998	Glance	385/24
5,796,890	8/1998	Tsuji et al.	385/24

Primary Examiner—Hemang Sanghavi
Attorney, Agent, or Firm—Eric R. Katz

[57] **ABSTRACT**

A bi-directional, redundant, optical transport system is configured to provide a non-blocking, bi-directional, multi-channel, protocol independent optical transport system for the simultaneous transfer of digital, analog, and discrete data between a plurality data terminal equipment. The optical transport system includes a light transmission line for transmitting light bi-directionally and a plurality of nodes, connected in series by the light transmission line for receiving, extracting and passing signal light. Each node comprises: data terminal equipment for issuing and receiving electrical signals; an electro-optical interface device, associated with the data terminal equipment, for converting electrical signals issued by the associated data terminal to signal light for insertion onto the light transmission line and for converting signal light, extracted from the light transmission line into electrical signals to be received by the associated data terminal; a translation logic device connected between the optical interface device and the data terminal equipment, for performing required protocol translation for the data terminal equipment and an optical interface device, connected to the electro-optical interface device and the light transmission line, for extracting signal light from the light transmission line to be converted into electrical signals by the electro-optical interface device for receipt by the data terminal equipment, for inserting, onto the light transmission line, signal light received from the electro-optical interface device and for passing signal light bi-directionally on the light transmission line.

18 Claims, 16 Drawing Sheets